



ALU-SAFE DP®

Winter Jacket, D3, E3, CAT 2

STYLE NUMBER	☞ TBA
DESCRIPTION	<ul style="list-style-type: none"> ☞ Open front jacket with press stud closure. ☞ Chinese collar with press studs. ☞ Two front pockets with flap and press stud closure. ☞ Two bottom, and two inner pockets. ☞ Hemmed sleeve ends with internal knitted cuff. ☞ Thermal liner for added warmth.
COLOUR	☞ Bayside Navy and International Orange.
SIZE	☞ XS – 6XL.
MATERIALS	☞ Fabric: Permanently flame resistant (FR) and arc-rated (AR) ALU-SAFE DP®.
APPLICATION	Work wear for the hot metal industry, especially primary Aluminium smelters and downstream Aluminium processors.
HAZARD ASSESSMENTS	Molten Aluminium and Cryolite splash, convective heat, radiant heat and flames. Thermal effects from electric arc flash, flames and flash fires.
FEATURES	<ul style="list-style-type: none"> ☞ Flame-resistant for the life of the garment. ☞ Highly moisture absorbent. ☞ Water / machine washable (see care label). ☞ Natural fibres. ☞ Comfortable to wear. ☞ Excellent breathability; absorbs perspiration and moisture.
STANDARDS	Fabric: <ul style="list-style-type: none"> ☞ EN ISO 11612 (A1, A2, B1, C1, D3, E3, F1). ☞ ASTM F1959, CAT 2 ☞ ATPV¹: 10 cal/cm²; HAF²: 80%

**WARNING: READ BEFORE USING THIS PRODUCT**

This product must be used as part of an appropriate set of PPC and PPE to protect against the hazards of arc flash. There may be exceptional cases in which even the best protection is not enough to prevent the harm caused by arc flash or the related effects, and although the product meets statutory and industry specifications, the use of this product does not guarantee that the product will provide complete protection in those exceptional cases. If you are in doubt or do not fully understand these limitations, contact the manufacturer for full information. The product may be returned to the supplier if you are not willing to accept a product that is subject to the limitations set out above.

DISCLAIMER:

The trademarks, literary and artistic works and all other forms of intellectual property displayed in this product information sheet are the lawful property of Charnaud & Co (Pty) Ltd, Charnaud (UK) Ltd and any other associated Charnaud entity. Any unauthorised use, distribution, reproduction, or variation of any content of this product information sheet, without the written consent of Charnaud & Co (Pty) Ltd, Charnaud (UK) Ltd and any other associated Charnaud entity would constitute a breach of its intellectual property rights. Charnaud & Co (Pty) Ltd, Charnaud (UK) Ltd and any other associated Charnaud entity all rights remain reserved. All information stated in Charnaud & Co (Pty) Ltd, Charnaud (UK) Ltd and any other associated Charnaud entity literature is only for guidance and cannot be considered as contractual. Charnaud & Co (Pty) Ltd, Charnaud (UK) Ltd and any other associated Charnaud entity is entitled to modify this information without notification and would not be obliged to supply products or materials that conform to those previously in force.

01-03-2022

Prepared by: V. Jugwanth

SOUTH AFRICA

Charnaud & Co (Pty) Ltd.
+27 (0)11 794 6040
sales@charnaud.co.za

EUROPE

Charnaud (UK) Ltd.
+44 (0)113 3507 651
sales@charnaud.uk

www.charnaud.net
CHARNAUD®